

Product Data Sheet SORB^{®XT} Oil Mat Blanks

Article	SORB ^{®XT} OM
Article No.	100613
Dimensions (mm)	30.000x800
Weight	10,90 Kg
Absorption capacity	192,00 L



Product Information:

Recommended use

- For use on solid ground surfaces (outside and inside)
- Selective protection of soil and factory grounds •
- Can be cut according to specific requirements
- Also, for preventive measures for longer periods
- Absorbs all kinds of oils, fuels, coatings, ٠ lubricants and other volatile substances

Application

Place the mat below the area, where contaminated substances are likely to spill (for example train tracks, factory sites or under large machinery and trucks)

After application

- Collect the contaminated blanks
- Dispose of following the respective valid laws and local regulations

Storage

Store in a dry place with low humidity

Properties

- Slip resistance
- PE-foil at bottom side prevents penetration in grounds
- Highly absorbent; can be thermally recycled
- Hydrophobic
- Similar to the Rail Mat but in a larger dimension



Allegro Capital, Logistics, Services & More GmbH

Klosterhofweg 64 41199 Mönchengladbach phone: +49 2166 1268-160 +49 2166 1268-260 fax: e-mail: service@sorb-global.de www.sorb-global.com managing director: Wolf-Peter Korth tax number: VAT number.: CRN:

102/5801/1903 DE308746153 19194



bank details: Commerzbank AG Mönchengladbach IBAN: DE82 3104 0015 0162 1028 00 BIC: COBADEFFXXX